

Broadband 101

16 July 2025


Tom Reid


Reid Consulting Group

<u>Tom@ReidConsultingGroup.com</u>

https://reidconsultinggroup.com

360 View of Broadband







Founded in 2006
Clients in 18 states
\$1.6 billion in project value
\$330 million in grant funding
6,000 miles of fiber expansion



Speeds



- 200/40 = 200 Mbps down/40 Mbps up
- 1000/200 = 1 Gbps down/200 Mbps up
- 5000/1000 = 5 Gbps down/1 Gbps up



- 200/200 = 200 Mbps down/200 Mbps up
- 1000/1000 = 1 Gbps down/1 Gbps up
- 5000/5000 = 5 Gbps down/5 Gbps up

1 Mbps = 1 million bits per second


1 Gbps = 1 billion bits per second



Underlying Infrastructure



"Coaxial Cable Copper"




"Twisted Pair Copper"





Long-Term Perspective

"Technology neutral" but must meet the speed requirements of 2055



Fixed Wireless Limitations from Terrain and Foliage





Wireless signals travel unobstructed across flat farmland, a feasible solution in these types of areas



In areas with rugged terrain and heavy foliage cover both coverage and capacity severely limited










Terrain Shadows

- 4 towers on high points, each 300' tall,
 3-5 miles apart to serve 50 square miles
- Many locations remain unreachable due to terrain shadows, without considering other obstructions or foliage
- Remaining households offer even a more difficult investment equation
- Low-orbit satellites such as Starlink require unobstructed view of the sky





Fixed Wireless and Satellite Capacity Limitations

- If the service area was flat and devoid of trees
- The fixed wireless and satellite networks could not support the load





Fiber-to-the-Premise: Aerial Example

Tremendous capacity


Stable services

High capital costs, low operating costs

30+ year lifetime

Foundation required for other services including mobile


Efficient use of investment




Once "cost to pass" covered, network is profitable except in very low density areas



Fiber Architecture Options for Passive Optical Networks




Distributed splits along feeder routes using terminals installed at transformers






Simplified Fiber Network Overview





Specifications Important





- Infrastructure projects require specifications
- Unlike roadway projects, broadband efforts have largely lacked detailed specifications
- Key topics such as strand count, installation in conduit vs. direct buried, depth of conduit, etc



Aerial



Area on Poles

Communications Space
Power Space (pole owner only)

Methods

Strand and Lash
Self-Supporting (ADSS*)

Major Cost Factors

Overlash Existing Facilities Make-Ready Strand Density


*ADSS = All-Dielectric Self-Supporting



Make-Ready Realities

Getting the existing poles ready for an additional attachment

- Clearance issues
- Age of poles





Make-Ready Improves Grid Resiliency





Building aerial fiber often also results in improved resiliency of the electric gird due to required pole replacements

Unpredictable variation in "make-ready" costs @ \$20,000 to \$55,000 per mile



Aerial Backbone and Distribution Fiber Budgetary Projections

Aerial Build per Mile	Low	High
Total Cost	\$75 <i>,</i> 000	\$120,000
Make-Ready	\$20,000	\$55,000
Fiber Build	\$55,000	\$65,000

- High Strand-Count
- Strand and Lash
- Third-Party Attacher
- No Overlash Option

- Big risk if budgeting too low
- Make-ready costs exceptionally variable

Incumbent Telcos have an overlash advantage



Underground



Methods

Boring (shown)
Trenching
Plowing

Major Cost Factors

In Conduit vs Direct Buried Rock Prevalence Depth



Underground Backbone and Distribution Fiber Budgetary Projections

Underground Build per Mile	Low @ 10% Rock	High @ 40% Rock
Total Cost	\$80,000	\$160,000
Fiber Build in Conduit	\$70,000	\$80,000
Rock Add	\$10,000	\$80,000

Big risk if budgeting too low In suitable soils, plowing fiber can reduce costs from the estimates above

- High Strand-Count
- Primarily Boring
- In Conduit
- Depth of 36"



Mystery Solved


Crowdsourced speed tests deliver:

- a. Concrete availability maps
- b. Progress tracking for accountability

Preponderance of evidence based on millions of test results



Ookla® Speedtest Intelligence® for Fixed Networks



Require ISPs to prove their capabilities





Debunking ISP Myths

Myth A: People in that area only subscribe to the low-speed packages

Reality: 25% to 33% of subscribers opt for the top speed offered.



Myth B: Bad tests are because of poor Wi-Fi

Reality: We drop speed tests with poor Wi-Fi signal strength.

We also included tests from GPS-enabled wired devices.




Myth C: People only run a test when there is a problem

Reality: We focus on the **maximum** speed tests. Network problems do prompt tests, as do resolutions of problems.











Ookla Locations – Palmyra Area







Ookla Locations – Palmyra Area



Clear Impact of the Funding



Ratings Change Also Clear Indication of Progress



Below 10/1

Above 10/1,
Below 25/3

Above 25/3,
Below 50/10

Above 50/10,
Below 100/20

Above 100/20,
Below 200/50

Above 200/50

Why do we need the Fabric?

- Addresses surprisingly unreliable
 - E-911 usually to the mailbox
 - Widely varied quality
 - No single-source-of-truth
- FCC contracted with CostQuest to:
 - Process satellite images and property records
 - Identify all Broadband Serviceable Locations (BSLs)
 - Intended to include all residential and small business locations
- Licensing complexities have limited the usefulness





Questions?

Tom Reid

Reid Consulting Group

<u>Tom@ReidConsultingGroup.com</u>

https://reidconsultinggroup.com

